FUJITSU

Data Sheet FUJITSU Tablet STYLISTIC V535 Industrial

Tough Tablet for Hard Work

The FUJITSU Tablet STYLISTIC V535 enables new levels of productivity in industrial settings. It is made for rough environments thanks to a water and dust resistant yet lightweight design and combined with a 21.0 cm (8.3-inch) display with toughened glass. Ultimate connectivity and navigation options like 4G/LTE, NFC, GPS and GLONASS as well as a long battery runtime let you stay connected wherever you are. Easy integration and security are enabled due to Windows 8.1 and TPM. The Fujitsu Smart Shell concept is designed to fit to individual industrial requirements.

Made for rough and tough environments

Discover new levels of productivity in industrial and retail settings.

Rugged water and dust resistant design based on IP65 rating, drop resistant up to 1.8 m (with rugged frame), medical wipeable and with an extended temperature range for outdoor use.

Highly adaptable for industrial use

Individualization to industry- and customer-specific requirements.

The Fujitsu Smart Shell concept includes a Smart Shell for Mounting to match industrial and transportation use. In addition to that, a Smart Shell with SmartCard reader does not only allow enhanced secure authentication, it also allows the user to read electronic patient cards in healthcare. A Smart Shell for retail is ready to hold a Chip & PIN reader to enable ePayment solutions. A cradle provides maximum comfort in the office.

Ultimate usability

Full-day productivity.

Bright IPS display with toughened glass and multi-touch support, even with gloves. Combined with a battery runtime of up to 6.5 hours. Built-in cameras and microphones allow easy collaboration.

Enterprise connectivity and navigation embedded.

Access to data from everywhere, even enabling professional and highly accurate navigation.

Optionally embedded 4G/LTE, NFC for real-time warehousing or contactless authentication, as well as GPS and GLONASS for highest navigation flexibility and accuracy.









Components

Base unit	STYLISTIC V535 - 64 GB	STYLISTIC V535 - 128 GB	STYLISTIC V535 - LTE - 128 GB
Operating systems			
Operating system	Windows 8.1 Pro 64-bit	Windows 8.1 Pro 64-bit	Windows 8.1 Pro 64-bit
Operating system compatible	Windows 8.1 Pro 64-bit	Windows 8.1 Pro 64-bit	Windows 8.1 Pro 64-bit
Hard disk drives			
Hard disk	64 GB eMMC	128 GB eMMC	
Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. Up to 20 GB of HDD space is reserved for system recovery Accessible capacity may vary, also depending on used software.		
Interface add on cards/components			
(optional)			
WLAN (optional)	Intel® Wireless-N 7265 2x2 b/g/n with integrated Bluetooth 4.0		
Multimedia			

Base unit

Base unit	STYLISTIC V535 - 64 GB	STYLISTIC V535 - 128 GB	STYLISTIC V535 - LTE - 128 GB	
General system information				
Processor	Intel® BayTrail-T™ SoC, Quad Core Inte	I® Atom™ Processor Z3795		
	(2.4 GHz, 2 MB)			
Chipset	Intel® BayTrail-™ SoC			
Supported capacity RAM	4 GB			
Memory slots	LPDDR3-1067 (1066MHz)			
Memory notes	Disclaimer: Up to 1 GB may not be available with 32-bit operating systems due to system resource requirements if system is preinstalled with 4 GB RAM			
LAN notes	GBit-LAN via USB conversion cable is limited to 480 Mbit/s due to USB 2.0 specification.			
Integrated WLAN	WLAN 802.11 a/b/g/n			
BIOS features	BIOS Flash EPROM Unified Extensible Firmware Interface (UEFI)			
Audio features	2x internal microphones, 2x built-in s	2x internal microphones, 2x built-in speakers (stereo)		
Waterproof / Spillproof	IP65			
Drop resistant	up to 1 m or up to 1.8 m (with rugged frame)			
Dustproof	IP65			
Disinfectable	yes (with medical wipes)			
Display				
Display	21.0 cm (8.3-inch),IPS,(WUXGA),Gla re,1,920 x 1,200 pixel,800:1,400 cd/ m ²	21.0 cm (8.3-inch),IPS,(WUXGA),Gla re,1,920 x 1,200 pixel,800:1,400 cd/ m ²	21.0 cm (8.3-inch),IPS,(WUXGA),Gla re,1,920 x 1,200 pixel,800:1,400 cd/ m ²	
Display notes	toughened glass	toughened glass	toughened glass	
Sensors	3-axis Accelerometer Compass Gyroscope Ambient Light Sensor	3-axis Accelerometer Compass Gyroscope Ambient Light Sensor	3-axis Accelerometer Compass Gyroscope Ambient Light Sensor Proximity	

Display				
Aspect ratio	16:10	16:10		16:10
Brightness - typical	400 cd/m ²	400 cd/m²		400 cd/m ²
Contrast - typical	800:1	800:1		800:1
Digitizer / Touch Technology	Multi-touch up to 10 fingers, active pen support	Multi-touch up to 1 pen support	0 fingers, active	Multi-touch up to 10 fingers, active pen support
Ambient light sensor	Integrated	Integrated		Integrated
Ambient light sensor notes	While enabled, the ambient light sensor automatically adjusts the display backlight	While enabled, the sensor automatical display backlight		While enabled, the ambient light sensor automatically adjusts the display backlight
Viewing angle (h/v) - typical	160°/160°	160°/160°		160°/160°
Graphics				
Base unit	STYLISTIC V535 - 64 GB	STYLISTIC V535 - 12	8 GB	STYLISTIC V535 - LTE - 128 GB
Max. resolution external display	up to 1,080p (1,920 x 1,080 pixel) via cradle or optional cable accessory	up to 1,080p (1,92 cradle or optional c		up to 1,080p (1,920 x 1,080 pixel) via cradle or optional cable accessory
Graphics features	Dual Display support (1x external, 1x internal) DirectX® 11 support Open GL® 3.2	Dual Display suppo internal) DirectX [®] 11 suppor Open GL [®] 3.2	rt (1x external, 1x	Dual Display support (1x external, 1x internal) DirectX [®] 11 support Open GL [®] 3.2
Interfaces				
DC-in	1		1	
Audio: line-out / headphone	1 (combo port with Audio line-in)		1 (combo port with	n Audio line-in)
Audio: line-in / microphone	1 (combo port with Audio line-out)		1 (combo port with	n Audio line-out)
Internal microphones	2 (digital)		2 (digital)	
USB 2.0 total	1		1	
USB 3.0 total	3 (on optional cradle)		3 (on optional crac	lle)
VGA	via optional adapter cable HDMI to VG	A only for cradle	via optional adapte	er cable HDMI to VGA only for cradle
HDMI	1 1 (on optional cradle or via optional	,		radle or via optional adapter cable)
Ethernet (RJ-45)	(on optional cradle or via optional ada			or via optional adapter cable)
Memory card slots	1 MicroSD (SD up to 2GB / SDHC up to 64GB)			o 2GB / SDHC up to 32GB / SDXC up to
SmartCard slot	optional via SmartCard Shell		optional via Smart	Card Shell
SIM card slot			1 (MicroSIM - only module (optional)	for models with integrated 4G/LTE)
Port Replicator interfaces (optional)				
Wireless technologies				
Antennas	2x dual band WLAN/BT, 1x NFC for ded	icated module		
Bluetooth	Bluetooth 4.0			
Integrated WLAN	WLAN 802.11 a/b/g/n			
WLAN notes	Import and usage according to country	-specific regulations		
Integrated LTE or UMTS				Huawei ME936 LTE with integrated GPS
LTE/UMTS/GPS notes	Including GPS functionality Import and usage according to country	/-specific regulations		LTE (800, 2600 MHz) Including GPS functionality
NFC	Yes			
GPS	AzureWave GPS-S23			
Power supply				
AC adapter	12V / 36W (3A)			
Rated voltage range	100 V - 240 V (AC Input)			
Rated frequency range	50 Hz - 60 Hz			
1st battery	Lithium polymer battery 2-cell, 16.8 Wh, 4425 mAh	Lithium polymer ba	attery 2-cell, 16.48V	Vh, 4425 mAh
Runtime 1st battery	up to 6.5h			
Battery charging time	3h via Cradle, 5h via USB charger			

Power supply				
Battery notes	Battery runtime information is based on worldwide acknowledged BAPCO Mobile Mark 2007 Benchmark (readers mode e.g. surfing the internet, writing E-mails, viewing documents) which provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity slightly decreases with every charging cycle and over the lifetime.			
Dimensions / Weight / Environmental				
Dimensions (W x D x H)	227.8 x 12.5 x 150.1 mm			
	8.97 x 0.49 x 5.91 inch			
Weight	from 540 g			
Weight (lbs)	from 1.19 lbs			
Operating ambient temperature	-10 - 50° C / -23.3° - 122° F			
Operating relative humidity	10 - 90 % (relative humidity)			
Temperature and humidity notes	During operation in the temerature range below 0°C battery will not be charged and LCD may react slowly. During operation in the temperature range above +45°C battery charging may be limited and camera noise may be increased			
Compliance				
Product	STYLISTIC V535 Industrial	STYLISTIC V535 Industrial		
Europe	CE! EN 60950	CE!		
Global	IT-Eco-Declaration RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment)			
Russia	GOST			
Compliance link	http://globalsp.ts.fujitsu.com/sites/ce	rtificates		
Additional Software				
Additional software (preinstalled)	Adobe® Reader® (pdf reader) CyberLink YouCam (webcam software Power Saving Utility Fujitsu Display Manager)		
Additional software (optional)	Drivers & Utilities DVD (DUDVD) Recovery DVD			
Manageability				
Manageability technology	PXE 2.1 Boot code			
Manageability link	http://www.fujitsu.com/fts/manageab	bility		
Security				
Physical Security	Kensington Lock on cradle or port replicator	Kensington Lock on cradle or port replicator	Kensington Lock on Cradle	
System and BIOS Security	Trusted platform module (TPM 1.2)	Trusted platform module (TPM 1.2)	Trusted platform module (TPM 1.2)	
User Security	BIOS security	BIOS security	BIOS security	
	User and supervisor BIOS password	User and supervisor BIOS password	User and supervisor BIOS password	

Warranty	
Warranty period	2 years (for countries within EMEIA)
Warranty type	Collect & Return Service / Bring-in Service (depending on country)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Product Support Services - the perfe	ct extension
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	3 years after end of product life
Service Weblink	htttp://ts.fujitsu.com/Supportservice

Recommended Accessories

Multifunctional Cradle STYLISTIC V535	Boosted efficiency, desktop experience, flexibility, expandability - these are only some of the benefits of the cradle for the STYLISTIC V535. The cradle is the perfect docking solution for STYLISTIC V535. In the office, in the warehouse or in the shop, it takes just a second to attach your device to the cradle and get connected to peripherals such as an external display, keyboard and mouse. Your workplace is simple and tidy while you are ready to work with your Fujitsu device.	Order Code: S26391-F2147-L100
Charging Cradle STYLISTIC V535	A charging cradle for use cases in the office or shared device sceanrios. The cradle is the perfect charging solution for STYLISTIC V535. In the office, in the warehouse or in the shop, it takes just a second to attach your device to the cradle and have it charged.	S26391-F2147-L200
Car Adapter USB	Frequent travelers need to charge their mobile devices anywhere. Simply plug the FUJITSU Car Adapter USB into the cigarette lighter socket and instantly feel the benefits of this device. This lightweight, easy to use FUJITSU Car Adapter USB maybe small, but its performance certainly isn't. It will keep your tablet PC and other mobile devices charged anywhere a 12 V power supply is available whether that be in your car or motor home.	Order Code: S26391-F2613-L617
Sleeve Case Mini	The FUJITSU Sleeve Case Mini is a thin tailored sleeve for your FUJITSU Tablet STYLISTIC V535. It protects against damage on the go, and brings a touch of style to your daily work. It can even be used as a stand if you need to display a presentation or watch a clip.	Order Code: S26391-F119-L322
Hand Strap for STYLISTIC V535	Carry and handle your tablet with comfort and ease with the FUJITSU Hand Strap. Designed for your STYLISTIC V535, it securely screws to the rear of the tablet for a firm grip and adjusts to fit your hand with a flexible Velcro overlap.	Order Code: S26391-F2148-L810
Shoulder Strap STYLISTIC V535	The Fujitsu Shoulder Strap is the perfect addition to your STYLISTIC V535 SmartCard Shells. The strap uses top quality materials and is highly adjustable, enabling you to transport your device with a minimum of effort and maximum comfort.	Order Code: S26391-F2148-L820
Active Pen for STYLISTIC V535	Annotate and fill in forms on your tablet with the premium, real size FUJITSU Active Pen at high resolution and accuracy with 256 pressure levels. Navigate, erase and right-click with the function button. Includes a battery and a pen holder to attach to the keyboard or tablet.	Order Code: S26391-F2148-L830
Rugged Frame for STYLISTIC /535	The rugged frame for the STYLISTIC V535 is the ideal add-on for even higher drop resistance of up to 1.8 meters. Its removable caps allow access to the Smart Shell and interfaces when the tablet is in the frame. (Pictures shows tablet for illustration purposes - tablet is not part of the package)	

Smart Shell with SmartCard for STYLISTIC V535



Fujitsu's Smart Shell concept allows to adapt the tablet to industry specificOrneeds and requirements. The Smart Shell with SmartCard reader deliversS2enhanced security and enables multi-factor authentication.S2

Order Code: S26391-F2149-L200

Mounting Kit for STYLISTIC V535



With the mounting solution for the STYLISTIC V535 the tablet can be securely mounted in a limitless number of use cases in industries like logistics, aviation and manufacturing. The Mounting Kit comprises the Smart Shell for Mounting and the Complementary Mounting Part for the STYLISTIC V535.

Order Code: S26391-F2149-L600

More information

Fujitsu OPTIMIZATION Services

In addition to FUJITSU Tablet STYLISTIC V535 Industrial, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Tablet STYLISTIC V535 Industrial, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/fts/tabletpc

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www. fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/ terms

© 2016 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

CONTACT

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com/fts 2016-03-31 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms

© 2016 Fujitsu Technology Solutions GmbH